DART SERVICE INSTRUCTION
TO AMEND INSTALLATION INSTRUCTIONS IIII-D139-799 REV. O OR LATER APPROVED REVISION AND INSTRUCTIONS FOR CONTINUED AIRWORTHINESS ICA-D139-799 REV. 14 OR LATER APPROVED REVISION

REF. FAA STC: SR02138SE REF. TCCA LOA C-11-0841 REF. EASA STC 10038656 REF. ANAC STC 2012S02-13 REF. JCAB STC-425-TYO REF. DGAC MEXICO STC IA-444/2017 REF. CHINA STC VSTC0869

1.0 PURPOSE

The purpose of this DART Service Instruction (DSI) is to provide customers with a shorter version of the D5245-7 Mounting Bolt used to install the DART D139-799-211/-212/-213 Quick Release Maintenance Step to prevent interference with the aircraft structure.

2.0 CHANGE

If the D5245-7 Mounting Bolt used to install the DART D139-799-211/-212/-213 Quick Release Maintenance Step interferes with the aircraft structure before bottoming out on the D5238-043 Lower Bracket, it is acceptable to replace the D5245-7 Mounting Bolt with the shorter D5245-9 Mounting Bolt. The DSI 9888-011 Alternative Mounting Bolt Kit is available from DART and includes a D5245-9 Mounting Bolt.

3.0 WEIGHT AND BALANCE

This DSI has a negligible effect on Weight & Balance.

4.0 PARTS LIST

Qty -011	Part Number	Description	
Х	X DSI 9888-011 ALTERNATE MOUNTING BOLT K		
1	1 D5245-9 MOUNTING BOLT		

Α	NEW ISSUE (REF. ECR 400)			SAD	22.06.06	
REV.		[DESCRIPTION	BY	DATE	
DESIGN		SAD	DART AEROSPACE		LTD	
DRAWN		SAD	HAWKESBURY, ONTARIO, CANADA			
CHECKED		MB	DSI 9888		REV. A	
MFG. APPR.		N/A			SHEET 1 OF 1	
APPROVED		CP "/	TITLE		SCALE	
DE APPR.		DS=	ALTERNATE MOUNTING E	BOLT K	IT NTS	
DATE 22.06.06		6.06	COPYRIGHT © 2022 BY DART AEROSPACE LTD. THIS DOCUMENT IS PRIVATE AND CONFIDENTIAL AND IS SUPPLIED ON THE EXPRESS CONDITION THAT IT IS NOT TO BE USED FOR MY PURPOSE OR COPIED OR COMMUNICATED TO ANY OTHER PERSON WITHOUT			